

**Technical data sheet · LÜTZE SUPERFLEX® TRONIC PUR**  
**Unshielded electronic cable UL recognized**  
**For highest requirements**



**PUR electronic cables · C-track compatible · Unshielded**

<b>Identification</b>	Type	SU TR PUR 15×0,25
	Part-No.	117028

**Use/Application/Characteristics**

Application	<ul style="list-style-type: none"> <li>• Robots, drag chains as well as everywhere where signals are transmitted to continuously moving system or machine parts</li> <li>• Machine and device construction, transport and conveyor technology, heating, climate technology</li> <li>• In dry and damp rooms</li> <li>• As monitoring, measurement and control cable for continuous flexing applications</li> </ul>
Characteristics	<ul style="list-style-type: none"> <li>• Low capacitance, very good electrical properties</li> <li>• Flame-retardant, self-extinguishing</li> <li>• Halogen-free, no corrosive gases</li> <li>• Very good flexing strength</li> <li>• Low adhesion, abrasion-resistant, nick-resistant, tear resistant</li> <li>• Hydrolysis-resistant, microbe-resistant, and rot-resistant</li> <li>• Good ruggedness and salt water resistance</li> <li>• Excellent coolant and lubricant resistance</li> <li>• Resistant to most oils, greases, alcohol-free benzines and kerosene</li> <li>• Silicone free</li> <li>• RoHS-compliant</li> </ul>

**Construction**

28.04.2017 – Subject to technical modification

Part-No. 117028

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SUPERFLEX<sup>®</sup> TRONIC PUR

## Unshielded electronic cable UL recognized

### For highest requirements

---

Description	SUPERFLEX TRONIC PUR
Number of conductors/cross-section	15×0.25
Jacket material	PUR
Jacket color	grey RAL 7001
Outer Ø	7.1 mm
Outer Ø	0.28 inches
Surface	adhesion-free matt
Weight	6.5 kg/100 m
Weight	46 Lbs/Mft
Cu-Index	3.5 kg/100 m
Cu-Index	24 Lbs/Mft

#### Element 1

Element construction	15×0.25
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 class 6
Conductor marking	Colour coded
Conductor marking standard	DIN 47100
Conductor insulation	Special TPE

#### overall construction

Overall stranding	Conductors stranded layers layer pitch optimised Conductors twisted without mechanical stress
Overall wrapping	Non-wovenmaterial
Jacket characteristics	Flame-retardant self-extinguishing Halogen free Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free

---

#### Technical data

Rated voltage	300 V
Test voltage type	AC 3000 V
Temperature according to UL	80 °C

28.04.2017 – Subject to technical modification

Part-No. 117028

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SUPERFLEX<sup>®</sup> TRONIC PUR

## Unshielded electronic cable UL recognized

### For highest requirements

Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	10×D
Minimum bending radius fixed	4×D

#### Element 1

Element construction	15×0.25
Insulation resistance at 20°C	1000 MΩ×km


#### Approvals/Standards

Approvals	UR
UL style	AWM 20549
Conformity	CE RoHS
Burning behavior according to	DIN EN 60332-2-2 UL 1581 Horizontal Flame Test
Oil resistant according to	DIN EN 60811-404
Halogen free according to	IEC 60754-1 DIN EN 60754-1

#### General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

#### Symbols



28.04.2017 – Subject to technical modification

Part-No. 117028

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk