

Technical data sheet · According to Allen-Bradley 2090 standard



Single Cable Assemblies for C-tracks

Identification	Type	2090-CSBM1DE-18AFxx
	Part-No.	193952.1000
System	Allen Bradley	
Allen Bradley designation*	2090-CSBM1DE-18AF10	

Use/Application/Characteristics

Application	<ul style="list-style-type: none">• Combined power supply cable with motor supply, brake and digital feedback especially for SERVO drives in machine and plant construction, transport and conveyor technology• Due to special PUR jacket and TPE / HGI conductor insulation optimally suited for c-tracks, extremely rough operating conditions and aggressive coolants and lubricants• Especially for industrial environments in mechanical and system engineering
Characteristics	<ul style="list-style-type: none">• High active and passive interference resistance (EMC)• Braided shield optimised for continuous flexible use• Very good alternating bending strength• Low adhesion, abrasion-resistant, nick-resistant, tear-propagation-resistant• Hydrolysis-resistant, microbe-resistant, and rot-resistant• Weatherproof, ozone and UV resistant (normal lighting conditions)• Good ruggedness and salt water resistance• Excellent coolant and lubricant resistance• Resistant to most oils, greases, alcohol-free benzines and kerosene• Halogen free• Silicone and talcum free• RoHS compliant

29.04.2017 – Subject to technical modification

Part-No. 193952.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - According to Allen-Bradley 2090 standard

Technical data

Number of conductors/cross-section	(4G1.0+(2×0.75)+(2×AWG22))
Number of conductors	8
Outer Ø	11.8 mm
Cable length	10 m
Rated voltage	1000 V 80 °C
Rated voltage U ₀ /U	600/1000
Test voltage	3000 V
Insulation resistance	> 500 MΩ × km
Temperature range fixed	-40 °C ... +80 °C
Temperature range moving	-25 °C ... +80 °C
Minimum bending radius fixed	5×D
Minimum bending radius moving	7.5×D
Burning behavior according to	VDE 0482 Part 265-2 DIN EN 50265-2 IEC 60332-1 UL 1581 Part 1080 VW-1 UL FT1
Halogen free according to	EN 50267-2-1
Approvals	cURus UL AWM 21223
Cable used	111599
Product photo	The product photos are not to scale and do not represent detailed images of the respective products.

Construction

Number of conductors/cross-section	(4G1.0+(2×0.75)+(2×AWG22))
Number of conductors	8
Conductor	CU-wire bare
Conductor category	Finely stranded DIN VDE 0295 IEC 60228, Class 6
Conductor marking	Power conductors black with numbered print U/L1/C/L+, V/L2, W/L3/D/L-
Control pair	colour-coded black, white with foil tape and braided shield
Conductor insulation	Special TPE
Overall stranding	Strands braided together
Overall shield	Braid shield Tinned copper wires optical cover approx. 85%
Jacket material	Special PUR
Surface	matt adhesion-free

29.04.2017 – Subject to technical modification

Part-No. 193952.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · According to Allen-Bradley 2090 standard

Jacket color orange RAL 2003

General

Note * Allen-Bradley article designations are registered trademarks of Rockwell Allen Bradley, and are for reference purposes only

Ordering instructions:

The LÜTZE Art. no. consists of two blocks that are separated by a dot:

6 digits before the dot: technical design

4 digits after the dot: length code in cm

Ex.: 198360.0500 corresponds to a length of 5.0 m

Special features:

- No minimum order quantity
- All intermediate lengths in steps of 0.5 m are available within a short time
- When ordering, please specify serial number and length key
- Additional types on request

29.04.2017 – Subject to technical modification

Part-No. 193952.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU


Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Symbols



29.04.2017 – Subject to technical modification

Part-No. 193952.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY