

Technical data sheet · According to SIEMENS-6FX8002 standard

Extension



Servo cable assemblies without brake pairs for C-tracks

Identification	Type	6FX8002-5CN05-1BA0
	Part-No.	198204.1000

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Extension cable for Siemens servo drives • Due to full PUR jacket and TPE conductor insulation optimally suited for c-tracks, extremely rough operating conditions, aggressive coolants and lubricants
Characteristics	<ul style="list-style-type: none"> • Silicone free • RoHS-compliant

Technical data

Number of strands/cross-section	(4G1.5)	
OD Ø	8.6 ca. mm	
Conductor marking	Power conductors black with numbered print U/L1/C/L+, V/L2, W/L3/D/L-	
UL approval	cURus	
Nominal voltage	1000 V 80 °C	
Voltage	U ₀ /U	0.6/1 kV
Test voltage	4000 V	
Insulation resistance	min. 500 MΩ × km	
Temperature range	moving	-25 °C to +80 °C
	fixed	-40 °C to +80 °C
Minimum bending radius	moving	D × 10
	fixed	D × 6

17.02.2017 – Subject to technical modification

Part-No. 198204.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · According to SIEMENS-6FX8002 standard

Extension

Burning behavior	Flame-retardant according to VDE 0482 T 265-2, DIN EN 50265-2, IEC 60332-1, UL 1581 section 1080 VW-1, CSA FT 1
Halogen free	according to DIN EN 50267-2-1, EN 60684-2
Product photo	The product photos are not to scale and do not represent detailed images of the respective products.

Construction

Conductor structure	Bare copper wire, finely stranded according to DIN VDE 0295 class 6, IEC 60228 class 6
Conductor insulation	Special TPE/HGI conductor insulation, UL
Conductor marking	Power conductors black with numbered print U/L1/C/L+, V/L2, W/L3/D/L-
Ground conductor	green/yellow according to DIN EN 50334
Stranding	Conductors cabled in layers without mechanical stress, optimised lay pitch
Banding	Fleece wrap over cable core
Overall shield	Braid from tinned copper wire, optical coverage $\geq 85\%$
Outer jacket	Full polyurethane jacket, matte, adhesion-free surface
Jacket color	orange RAL 2003

General

Note	* Siemens article designations are registered trademarks of Siemens AG, and are for reference purposes only
------	---

Ordering instructions:

The LÜTZE Art. no. consists of two blocks that are separated by a dot:

6 digits before the dot: technical design

4 digits after the dot: length code in cm

Ex.: 198360.0500 corresponds to a length of 5.0 m

Special features:

- No minimum order quantity
- All intermediate lengths in steps of 0.5 m are available within a short time
- When ordering, please specify serial number and length key
- Additional types on request

Comments

Notes:

- The extension can also be used for **SPEED-CONNECT** plug connection, for this the O-ring must be removed on the outer thread. This does not affect the tightness of the plug connection.
-

Symbols

17.02.2017 – Subject to technical modification

Part-No. 198204.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · According to SIEMENS-6FX8002 standard
Extension



17.02.2017 – Subject to technical modification

Part-No. 198204.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk