

Technical data sheet · Plastic and metal accessory sealing insert ASI DE

Cable fittings and accessories



Identification	Type	MFDE ASI PG13,5 10×4
	Part-No.	600120
Use/Application/Characteristics		
Application	<ul style="list-style-type: none">• For retroactive installation of our cable fittings• Cable dimensions: 4.0 mm × 10.0 mm +/- 0.2 mm• Suitable for installation with the following types:<ul style="list-style-type: none">TOP TP PG 13.5TOP TP M 20TOP T PG 13.5TOP T M 20	
Characteristics	<ul style="list-style-type: none">• Seal insert for ASI bus cables	
Technical data		
Outer Ø	15.2 mm	
Thread G	PG 13.5	
Construction		
Description	MFDE ASI PG13.5 10×4	
Material	TPE	
General		
PU	100 Quantity	

28.01.2017 – Subject to technical modification

Part-No. 600120

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Plastic and metal accessory sealing insert ASI DE


Note

Cable dimensions:
4.0 mm × 10.0 mm +/- 0.2 mm

Suitable for installation with the following types:

TOP TP PG 13.5
TOP TP M 20
TOP T PG 13.5
TOP T M 20

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600120

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk