

Technical data sheet · Metal fitting with shield termination TOP-T-S-EMV2

Cable fittings and accessories



| | | |
|--|--|-------------------------|
| Identification | Type | TOP-T-S-EMV2 MS M63×1,5 |
| | Part-No. | 600377 |
| Use/Application/Characteristics | | |
| Characteristics | <ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket• O-ring and EMC compliant shield termination• The braided shield is automatically contacted when mounting the screw connection. | |
| Technical data | | |
| Clamping range D | 34 – 44 mm | |
| Protection class | IP68 | |
| | Up to 5 bar | |
| Thread form | metric | |
| Thread G | M 63×1.5 | |
| SW 1 | 64 mm | |
| SW 2 | 68 mm | |
| L | 64.3 mm | |
| L1 | 14 mm | |
| Construction | | |
| Description | TOP-T-S-EMC2 MS M63 x 1.5 | |
| Material | Brass nickel-plated | |

28.01.2017 – Subject to technical modification

Part-No. 600377

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Metal fitting with shield termination TOP-T-S-EMV2

| | |
|-----------------------|-----------|
| Material O-ring | Perbunan® |
| Material sealing ring | NBR |

General

| | |
|----|------------|
| PU | 5 Quantity |
|----|------------|

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600377

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY