

## Technical data sheet · Plastic NPT

---



---

<b>Identification</b>	Type	NPT 3/4"
	Part-No.	600442D

---

<b>Use/Area of application</b>	
Properties	<ul style="list-style-type: none"><li>• Integrated strain relief</li><li>• Wide sealing and clamping range</li><li>• Easy to install</li></ul>

---

<b>Technical data</b>	
Temperature range	-20 °C to +100 °C +14 to +212 F
Protection class	IP68 – 5 bar
Gasket	Polychloroprene-Nitrile rubber CR/NBR
Connecting thread	Connecting thread NPT

---

<b>Design</b>	
H	7.0 mm
SW 1 = across flats	36 mm
Internal thread	NPT

---

<b>General</b>	
Comments	For secure tightening of cable glands and accessories

---

08.12.2012 – Subject to technical modification

Part-No. 600442D

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com


United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk

# Technical data sheet · Plastic NPT

---

## Dimensions



08.12.2012 – Subject to technical modification

Part-No. 600442D

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY