

Technical data sheet · Plastic fittings TOP-T-P, metric version

Cable fittings and accessories



Identification	Type	TOP-T-P M32×1,5 GR
	Part-No.	600683
Use/Application/Characteristics		
Characteristics	<ul style="list-style-type: none">• – metric –• Cable fitting with hexagon base• Strain relief and seal	
Technical data		
Clamping range D	11 – 21 mm	
Approvals	UL	
Protection class	IP68	
	Up to 5 bar	
Thread form	metric	
Thread G	M 32×1.5	
SW	36 mm	
L1	11 mm	
Construction		
Description	TOP-T-P M32×1.5 GR	
Material	PA 6.6-V-2	
Material sealing ring	NBR	
Color	grey RAL 7001	

28.01.2017 – Subject to technical modification

Part-No. 600683

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Plastic fittings TOP-T-P, metric version

General

PU

25 Quantity

Dimensions



Symbols



28.01.2017 – Subject to technical modification

Part-No. 600683

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY