

Technical data sheet · Plastic cable fitting TOP-TR-P metric

Cable fittings and accessories



Identification	Type	TOP-TR-P M25×1,5 GR
	Part-No.	600692

Use/Application/Characteristics

Characteristics	<ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief and gasket• Reduced sealing insert• Reduced clamping range
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Technical data

Clamping range D	5 – 14 mm
Protection class	IP68
	Up to 5 bar
Thread form	metric
Thread G	M 25×1.5
SW	28 mm
L1	11 mm

Construction

Description	TOP-TR-P M25×1.5 GR
Material	PA 6.6-V-2
Material sealing ring	NBR
Color	grey RAL 7001

28.01.2017 – Subject to technical modification

Part-No. 600692

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Plastic cable fitting TOP-TR-P metric

General

PU

50 Quantity

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600692

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY