

Technical data sheet · Metal fitting TOP-TR

Cable fittings and accessories



| | | |
|--|---|-------------------|
| Identification | Type | TOP-TR MS M50×1,5 |
| | Part-No. | 600707 |
| Use/Application/Characteristics | | |
| Characteristics | <ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket and O-Ring• Reduced sealing insert• Reduced Clamping range | |
| Technical data | | |
| Clamping range D | 21 – 29 mm | |
| Protection class | IP68 | |
| | Up to 5 bar | |
| Thread form | metric | |
| Thread G | M 50×1.5 | |
| SW 1 | 54 mm | |
| SW 2 | 54 mm | |
| L | 52 mm | |
| L1 | 9 mm | |
| Construction | | |
| Description | TOP-TR MS M50×1.5 | |
| Material | Brass nickel-plated | |

28.01.2017 – Subject to technical modification

Part-No. 600707

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Metal fitting TOP-TR

| | |
|-----------------------|-----------|
| Material O-ring | Perbunan® |
| Material sealing ring | NBR |

General

| | |
|----|------------|
| PU | 5 Quantity |
|----|------------|

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600707

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk