

Technical data sheet · Metal fitting TOP-T

Cable fittings and accessories



Identification	Type	TOP-T MS PG9
	Part-No.	600711

Use/Application/Characteristics

Characteristics	<ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket and O-Ring
-----------------	---

Technical data

Clamping range D	5.5 – 10 mm
Protection class	IP68
	Up to 5 bar
Thread form	PG
Thread G	PG 9
SW 1	17 mm
SW 2	17 mm
L	28 mm
L1	6 mm

Construction

Description	TOP-T MS PG9
Material	Brass nickel-plated
Material O-ring	Perbunan®
Material sealing ring	NBR

28.01.2017 – Subject to technical modification

Part-No. 600711

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Metal fitting TOP-T

General

PU

100 Quantity

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600711

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY