

# Technical data sheet · Metal fitting TOP-TR

Cable fittings and accessories



<b>Identification</b>	Type Part-No.	TOP-TR PG 42 600738
<b>Use/Area of application</b>		
Properties	<ul style="list-style-type: none"><li>• Cable fitting with hexagon base</li><li>• Strain relief</li><li>• Gasket and O-Ring</li><li>• With reduced sealing insert</li></ul>	
<b>Technical data</b>		
Strain relief	Yes	
Material	Brass nickel-plated	
Protection class	IP 68 to 5 bar	
Anti-kink device	without anti-kink device	
Gasket	Neoprene	
O-Ring (OR)	Perbunan®	
Clamping range D	23.0 – 31.0 mm	
weight approx.	32.38 kg/100 piece	
Thread	PG 42	
<b>Design</b>		
G	PG 42	
L 1	12.0 mm	
L	59.7 mm	

08.12.2012 – Subject to technical modification

Part-No. 600738

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

## Technical data sheet · Metal fitting TOP-TR

---

SW 1 = across flats                      58 mm  
SW 2 = across flats                      58 mm


---

### General

PU    12 piece

---

### Dimensions



08.12.2012 – Subject to technical modification

Part-No. 600738

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223  
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2  
www.lutze.com · sales.gb@lutze.co.uk