

Technical data sheet · TOP-T-P black

Cable fittings and accessories



Identification	Type	TOP-T-P PG9 SW
	Part-No.	600861
Use/Application/Characteristics		
Characteristics	<ul style="list-style-type: none">• – PG –• Cable fitting with hexagon base• Strain relief and seal	
Technical data		
Clamping range D	4 – 8 mm	
Protection class	IP68	
	Up to 5 bar	
Thread form	metric	
Thread G	PG 9	
SW	19 mm	
L1	8 mm	
Construction		
Description	TOP-T-P PG9 SW	
Material	PA 6.6-V-2	
Material sealing ring	NBR	
Color	black RAL 9005	
General		

28.01.2017 – Subject to technical modification

Part-No. 600861

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Technical data sheet · TOP-T-P black

PU

50 Quantity

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600861

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY