

Technical data sheet · Metal fittings TOP-M EExe

Cable fittings and accessories



Identification	Type	TOP-MEEExe PG 16
	Part-No.	600914
Use/Area of application		
Application	<ul style="list-style-type: none">• For explosion risk areas	
Properties	<ul style="list-style-type: none">• Ex cable fitting with hexagon base• Strain relief and gasket	
Technical data		
Strain relief	Yes	
Material	Brass nickle-plated for explosion risk areas according to EN 50014	
Protection class	IP 68 to 5 bar	
Gasket	Neoprene	
O-Ring (OR)	Perbunan®	
Clamping range D	10.0 – 14.0 mm	
weight approx.	3.14 kg/100 piece	
Thread	PG 16	
Design		
G	PG 16	
L 1	6.5 mm	
SW	24 mm	

03.10.2009 – Subject to technical modification

Part-No. 600914

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.


Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Metal fittings TOP-M EExe

General

PU 50 piece

Dimensions



03.10.2009 – Subject to technical modification

Part-No. 600914

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk