

Technical data sheet · Plastic fitting TOP-K Ex metric

Cable fittings and accessories



Identification	Type	TOP-K Ex M 63 × 1,5
	Part-No.	601727

Use/Area of application

Properties	<ul style="list-style-type: none">• Ex cable fitting with hexagon base• Strain relief, gasket and O-Ring• For explosion risk areas according to EN 50014• Installation-friendly• Suitable for the fixed running of cables• (Ignition) Protection class: Ex e - increased safety• (Ignition) Protection class: Ex tD A21 - housing protection• Category / Zone: 2G and 2D / 1, 2, 21, 22
------------	--

Technical data

Strain relief	Yes
Material	Polyamide
Colour	blue/black RAL 5015/RAL 9005; black/black RAL 9005
Protection class	IP 66
Anti-kink device	without anti-kink device
Gasket	Neoprene
O-Ring (OR)	Perbunan®
Clamping range D	27.0 – 48.0 mm
weight approx.	9.60 kg/100 piece
Thread	M 63

09.12.2012 – Subject to technical modification

Part-No. 601727

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Plastic fitting TOP-K Ex metric


Design

G	M 63×1.5
L 1	12.0 mm
SW	68 mm

General

PU	5 piece
----	---------

Dimensions



09.12.2012 – Subject to technical modification

Part-No. 601727

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY