



Identification	Type	WAA 6-1931
	Part-No.	751931
Input		
Measurement input	AC/DC 0–5 A, ±5 A true RMS	
Galvanic insulation I/O	3-way isolation	
Zero /Span	Production comparison	
Line frequency	4 Hz – 20 Hz	
Input resistance	<0.1 Ω, max. 10 A (30 s)	
Load Side		
Max. load impedance at I-output	400 Ω	
Ripple	<5 mV _{eff}	
General		
Nominal voltage	AC/DC 24–240 V	
Operation voltage range	DC: 16.8–264 V, AC: 19.2–264 V	
Rated current	10.0 mA	
Status Indication	LED yellow	
Input/output protection	AC/DC 30 V overvoltage, current input with Varistor, short circuit-proof output	
Accuracy	< 0.5 % FSR	
Linearity error	< 0.1 % FSR	
Temperature coefficient	<150 ppm / K FSR	

03.04.2016 – Subject to technical modification

Part-No. 751931

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LUTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY


Technical data sheet · Interface Technology

Insulation voltage input/output	4.0 kV _{eff}
Housing material	PPE
Field installation	rail TS 35 (EN 50022)
Protection class	IP 20
Installation position	Optional
Termination	Spring terminal : 0.14 - 2.5 mm ² (with AE 1.5 mm ²)
Operation temperature range	-25 °C – 60 °C
Storage temperature range	-40 °C – 85 °C
Dimensions (w × h × d)	17.5 × 79.0 × 84.0 mm
Weight (kg/piece)	0.070 kg/piece

Dimensions



PIN assignment



Accessories

Accessories	Color	Article number	Type	PU
Tag holder 7×20 mm	white	760968	BZT-0720	100
Laser printer label 6.35×15.24 mm (sheet with 528 labels)		681033	LEB-0615	1

03.04.2016 – Subject to technical modification

Part-No. 751931

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LUTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY