



<b>Identification</b>	Type	LCIS-RS24UP-S-1U
	Part-No.	760021.1000

<b>Description</b>	Output Relay Interface, relay with 1 directional contact, pluggable AC/DC 250 V, 6 A, 1500 VA
--------------------	--

<b>Input</b>	
Rated voltage $U_N$	AC/DC 24 V
Input voltage range	19.2 – 30 V
Rated frequency	50 – 60 Hz
Rated current $I_N$	13 mA
Interrupting voltage	<2.0 V
Protection device	Bridge rectifier
Max. length of connecting lead	DC: 1000 m / AC: 500 m
Status display input	LED green

<b>Output</b>	
Contact type	1 changeover contacts
Switching element	Relays
Min. switching voltage	AC/DC 17 V
Max. switching voltage	AC/DC 250 V
Min. switching current	AC/DC 5 mA

25.08.2017 – Subject to technical modification

Part-No. 760021.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



## Technical data sheet - Interface Technology

---

Max. switching current	AC/DC 6 A
Switching capacity DC 13	1 A @ 24 V 200 mA @ 125 V 100 mA @ 250 V
Switching capacity AC 15	3 A
Max. switching capacity	1500 VA / 30 W
Contact material	AgSnO <sub>2</sub>
Mechanical service life	> 5 x 10 <sup>7</sup> operations
Switch-on delay	AC: 10 ms, DC: 6 ms
Shutdown delay	AC: 10 ms, DC: 10 ms
Clearance/creep. dist. (control/load side)	>5.5 mm
Protection device	none

---

### General

---

Housing material	PA 6.6 (UL 94 V-0)
Colour of the housing	RAL 7012 basalt grey
Protection class	IP20
Mounting	DIN rail mountable TS35 (EN 60715)
Installation position	any
Insulation voltage input / output	AC 4.0 kV <sub>eff</sub>
Safe isolation	yes
Operation temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +80 °C
Dimensions (w x h x d)	6.2 x 90.0 x 76.0 mm
Weight	0.035 kg/piece
Connection device	Screw terminal single wire 0.25 mm <sup>2</sup> -2.5 mm <sup>2</sup> / AWG 20-14 fine stranded wire with ferrule 0.25 mm <sup>2</sup> -1.5 mm <sup>2</sup> / AWG 20-16
Standards	EN 60947-5-1
Approvals	cULus DNV GL

25.08.2017 – Subject to technical modification

Part-No. 760021.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com


United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Dimensions



PIN assignment



25.08.2017 – Subject to technical modification

Part-No. 760021.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk