



Identification	Type	LCIS-RS120UP-S-1U
	Part-No.	760051.1000
Description	Output Relay Interface, relay with 1 directional contact, pluggable AC/DC 250 V, 6 A, 1500 VA	
Input	Rated voltage U_N AC/DC 115 V Input voltage range 92 – 126.5 V Rated frequency 50 – 60 Hz Rated current I_N 5 mA Interrupting voltage <7.7 V Protection device Bridge rectifier Max. length of connecting lead DC: 1000 m / AC: 500 m Status display input LED green	
Output	Contact type 1 changeover contacts Switching element Relays Min. switching voltage AC/DC 17 V Max. switching voltage AC/DC 250 V Min. switching current AC/DC 5 mA	

25.08.2017 – Subject to technical modification

Part-No. 760051.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



Technical data sheet · Interface Technology

Max. switching current	AC/DC 6 A
Switching capacity DC 13	1 A @ 24 V 200 mA @ 125 V 100 mA @ 250 V
Switching capacity AC 15	3 A
Max. switching capacity	1500 VA / 30 W
Contact material	AgSnO ₂
Mechanical service life	> 5 × 10 ⁷ operations
Switch-on delay	8 ms
Shutdown delay	13 ms
Clearance/creep. dist. (control/load side)	>5.5 mm
Protection device	none

General

Housing material	PA 6.6 (UL 94 V-0)
Colour of the housing	RAL 7012 basalt grey
Protection class	IP20
Mounting	DIN rail mountable TS35 (EN 60715)
Installation position	any
Insulation voltage input / output	AC 4.0 kV _{eff}
Safe isolation	yes
Operation temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +80 °C
Dimensions (w × h × d)	6.2 × 90.0 × 76.0 mm
Weight	0.035 kg/piece
Connection device	Screw terminal single wire 0.25 mm ² –2.5 mm ² / AWG 20–14 fine stranded wire with ferrule 0.25 mm ² –1.5 mm ² / AWG 20–16
Standards	EN 60947-5-1
Approvals	cULus DNV GL

25.08.2017 – Subject to technical modification

Part-No. 760051.1000

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
www.lutze.com · info@lutze.com


United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Dimensions



PIN assignment



25.08.2017 – Subject to technical modification

Part-No. 760051.1000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY