

Technical data sheet · Modular housing system

LCOS Modular housing system

Identification	Type	LCOS-FTE-PE-575-PN-00-1
	Part-No.	780730.575.1

Use/Application/Characteristics

Description	Function carrier 22.5 mm, with supply DC 24 V, 2×RJ45, with PE direct contact, ready for connection
-------------	---

General

Dimensions (w × h × d)	57.5 × × mm
Material	Polyamid PA 6.6 (UL 94 V0, NFF I2, F2)
Field installation	on TS 35 with interlock, DIN 60715

Standards

Loads from pollutants IEC 60068-2-42, IEC 60068-2-43
Insulation coordination EN 60064-1, EN 60947-1, EN 50175, EN 50124-1
Shock resistance 15 G/11 ms, IEC 60068-2-27
Vibration resistance 4 G, IEC 60068-2-8

12.11.2014 – Subject to technical modification

Part-No. 780730.575.1

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY