

Identification	Type	LCOS-ZB-DM-225-12-00-1
	Part-No.	780900.225.2

Description	LCOS data module
	12-pin
	22.5 mm

Use/Application/Properties	
Description	Data module 22.5 mm

Data module	
Material PCB	FR4
Material connector	PE-HT
Operating voltage	max. DC 30 V
Operating current	max. DC 2 A/contact
System current	max. DC 8 A
Pole number	Input/output: 12-ping, outlet: 2×10-pin

General	
Connection device	Data bridge 12-pole
Mounting	latches into position on LCOS function carrier 22.5 mm

25.08.2017 – Subject to technical modification

Part-No. 780900.225.2

USA: LUTZE INC.
13330 South Ridge Drive · Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk


Technical data sheet - Load monitoring

Contact material	CuZn
Dimensions (w x h x d)	36.0 x 10.0 x 19.0 mm
Weight	0.004 kg/piece
Standards	IEC 60068-2-42, 43, 8, 27 EN 60064-1 EN 50175 EN 50124-1
Approvals	UR
PU	10 piece

General ambient conditions

Operation temperature range	-40 °C ... +85 °C
Storage temperature range	-40 °C ... +85 °C
Relative air humidity	5 % – 95 % without condensation
Protection class	IP20
Shock resistance	15 g 11 ms acc. to IEC 60068-2-27
Vibration resistance	4 g acc. to EN 60068-2-8

Dimensions



25.08.2017 – Subject to technical modification

Part-No. 780900.225.2

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY