

# Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals



Flexible electronic cable · Unshielded

<b>Identification</b>	Type	LIYY 2×AWG22 UL/PLTC
	Part-No.	A3032202

## Use/Application/Characteristics

Application	<ul style="list-style-type: none"> <li>• <b>Industrial grade PLTC</b> electronic cable for machine tools, process instrumentation and controls, computer peripherals, HVAC technology, assembly and production lines, low voltage interconnect and other industrial applications including <b>installation in cable trays</b></li> </ul>
Characteristics	<ul style="list-style-type: none"> <li>• Flexible for easy installation</li> <li>• Easy strip design</li> <li>• Color coded conductors</li> <li>• Specially formulated jacket for oil resistance</li> <li>• Premium durability</li> <li>• Extended temperature range</li> <li>• <b>UL listed</b> and <b>NFPA 79</b> compliant</li> </ul>

## Construction

Description	ELECTRONIC PLTC PVC
Number of conductors/cross-section	2×AWG22
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	4.4 mm
Outer Ø	0.172 inches
Weight	17 Lbs/Mft

24.03.2017 – Subject to technical modification

Part-No. A3032202

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals

---

Cu-Index 4 Lbs/Mft

## Element 1

Element construction AWG22/2C  
Conductor construction AWG 22 (19/34)  
Conductor AWG conductor  
CU-wire tin-plated  
Conductor category feindrähtig  
Conductor marking black  
brown  
Conductor insulation SR-PVC

## overall construction

Jacket characteristics Flame-retardant  
Oil resistant  
Silicone-free

---

## Technical data

Rated voltage UL 300 V  
Temperature range fixed -25 °C ... +105 °C  
Minimum bending radius fixed 4×D

## Element 1

Element construction AWG22/2C

---

## Approvals/Standards

Approvals cULus  
PLTC  
UL Type CM  
cURus  
AWM II A/B  
NEC 725, 760, 800  
Class 1 Div. 2 (PLTC use only)  
UL style AWM 2464  
Conformity CE  
REACH  
RoHS  
Burning behavior according to UL VW-1  
UL FT4  
Oil resistant according to Oil Res II

---

## General

---

24.03.2017 – Subject to technical modification

Part-No. A3032202

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

## Symbols



24.03.2017 – Subject to technical modification

Part-No. A3032202

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk