

Technical data sheet · LÜTZE SILFLEX® N PVC CONTROL TRAY CABLE

With approvals for North America according to NEC, NFPA 79 and UL 508A



PVC control cables · unshielded

Identification	Type	SI N TRAY-ER 25×AWG18 GR
	Part-No.	A3081825

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Multi-conductor control cables with TC-ER „Exposed Run“ approval • Machine and device construction, transport and conveyor technology, HVAC technology • Compliant with NFPA 79 standards • „TC-ER“ for use on machines and in open cable ducts • „WTTC“ Wind Turbine Tray Cable for use in wind turbines • „MTW“ Machine Tool Wire • „PLTC-ER“ Power Limited Tray Cable – Exposed Run • „ITC-ER“ Instrumentation Tray Cable – Exposed Run • In dry, moist and wet rooms
Characteristics	<ul style="list-style-type: none"> • Flexible wires with nylon for better resistance to pressure and impacts as per UL 1277 • Easy stripping and fast installation • Very flexible flexibility for complex installation distances and small bending radii • Improved oil resistance due to specifically developed PVC jacket • Sunlight-resistant • „Direct burial“ for installation in the ground • Silicone free • RoHS compliant

Construction

29.01.2017 – Subject to technical modification

Part-No. A3081825

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SILFLEX® N PVC CONTROL TRAY CABLE

With approvals for North America according to NEC, NFPA 79 and UL 508A

Description	SILFLEX CONTROL CABLE PVC
Number of conductors/cross-section	25×AWG18
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	17.2 mm
Outer Ø	0.677 inches
Weight	46.7 kg/100 m
Weight	314 Lbs/Mft
Cu-Index	22.5 kg/100 m
Cu-Index	151 Lbs/Mft

Element 1

Element construction	AWG18/25C
Conductor construction	AWG 18 (19/30)
Conductor	AWG conductor CU-wire bare
Conductor category	feindrähtig
Conductor marking	black with white number print green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

overall construction

Jacket characteristics	Oil resistant Silicone-free
------------------------	--------------------------------

Technical data

Rated voltage	600 V TC-ER/MTW 1000 V WTTC
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	4×D

Element 1

Element construction	AWG18/25C
----------------------	-----------

Approvals/Standards

29.01.2017 – Subject to technical modification

Part-No. A3081825

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SILFLEX® N PVC CONTROL TRAY CABLE


With approvals for North America according to NEC, NFPA 79 and UL 508A

Approvals	TC-ER W TTC PLTC-ER ITC-ER cURus cULus UL Type MTW or DP-1 Class 1 Div. 2 per NEC Art. 336, 392, 501 CIC FT4 cUL TC UL 1277
UL style	AWM 20886
Conformity	CE REACH RoHS
Oil resistant according to	Oil Res II

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



29.01.2017 – Subject to technical modification

Part-No. A3081825

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY