

Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC with UL/CE/PTLC Approvals



Flexible electronic cable · Shielded

Identification	Type	LIY(C)Y (20×AWG22) UL/CSA/CE/PLTC
	Part-No.	A3132220

Use/Application/Characteristics

Application	• Double shielded industrial grade PLTC electronic cable for machine tools, process instrumentation and controls, computer peripherals, HVAC technology, assembly and production lines, low voltage interconnect and other industrial applications including installation in cable trays
Characteristics	• Flexible for easy installation • Easy strip design • Color coded conductors • Specially formulated jacket for oil resistance • Premium durability • Extended temperature range • UL listed and NFPA 79 compliant

Construction

Description	ELECTRONIC (C) PLTC PVC
Number of conductors/cross-section	20×AWG22
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	9.4 mm
Outer Ø	0.369 inches
Weight	109 Lbs/Mft

24.03.2017 – Subject to technical modification

Part-No. A3132220

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC with UL/CE/PTLC Approvals

Cu-Index	62 Lbs/Mft
Element 1	
Element construction	AWG22/20C
Conductor construction	AWG 22 (19/34)
Conductor	AWG conductor CU-wire tin-plated
Conductor category	feindrähtig
Conductor marking	black brown red orange yellow green blue violet grey white white/black white/brown white/red white/orange white/yellow white/green white/blue white/violet white/grey white/black/brown
Conductor insulation	SR-PVC
overall construction	
Drain wire	CU-wire tin-plated
Overall shield	Aluminium laminate Foil shield Braid shield Tinned copper wires
Jacket characteristics	Flame-retardant Oil resistant Silicone-free

Technical data

Rated voltage UL	300 V
Temperature range fixed	-25 °C ... +105 °C
Minimum bending radius fixed	6×D

24.03.2017 – Subject to technical modification

Part-No. A3132220

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC with UL/CE/PTLC Approvals

Element 1

Element construction

AWG22/20C


Approvals/Standards

Approvals	cULus PLTC UL Type CM cURus AWM II A/B NEC 725, 760, 800 Class 1 Div. 2 (PLTC use only)
UL style	AWM 2464
Conformity	CE REACH RoHS
Burning behavior according to	UL VW-1 UL FT4
Oil resistant according to	Oil Res II

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



24.03.2017 – Subject to technical modification

Part-No. A3132220

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY