

# Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC TPC with twisted pairs and UL/CE/PTLC Approvals



Flexible electronic cable · Shielded

<b>Identification</b>	Type	LIY(C)PVC TP (4×2×AWG22)UL/cURus/CE/PLTC
	Part-No.	A3142208

## Use/Application/Characteristics

Application	<ul style="list-style-type: none"> <li>• <b>Double shielded industrial grade PLTC</b> electronic cable for machine tools, process instrumentation and controls, computer peripherals, HVAC technology, assembly and production lines, low voltage interconnect and other industrial applications including <b>installation in cable trays</b></li> </ul>
Characteristics	<ul style="list-style-type: none"> <li>• Flexible for easy installation</li> <li>• Easy strip design</li> <li>• Color coded conductors</li> <li>• Conductors twisted in pairs</li> <li>• Specially formulated jacket for oil resistance</li> <li>• Premium durability</li> <li>• Extended temperature range</li> <li>• <b>UL listed</b> and <b>NFPA 79</b> compliant</li> </ul>

## Construction

Description	ELECTRONIC (C) PLTC PVC TP
Number of conductors/cross-section	8×AWG22
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	7.7 mm

10.03.2017 – Subject to technical modification

Part-No. A3142208

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC TPC with twisted pairs and UL/CE/PTLC Approvals

---

Outer Ø	0.305 inches
Weight	62 Lbs/Mft
Cu-Index	31 Lbs/Mft

## Element 1

Element construction	AWG22/4TP
Conductor construction	AWG 22 (19/34)
Conductor	AWG conductor CU-wire tin-plated
Conductor category	feindrähtig
Conductor marking	white black white brown white red white orange
Conductor insulation	SR-PVC
Stranding	Conductors stranded in pairs

## overall construction

Drain wire	CU-wire tin-plated
Overall shield	Aluminium laminate Aluminium laminate Braid shield Tinned copper wires
Jacket characteristics	Flame-retardant Oil resistant Silicone-free

---

## Technical data

Rated voltage UL	300 V
Temperature range fixed	-25 °C ... +105 °C
Minimum bending radius fixed	6×D

## Element 1

Element construction	AWG22/4TP
----------------------	-----------

---

## Approvals/Standards

---

10.03.2017 – Subject to technical modification

Part-No. A3142208

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC (C) PLTC PVC TPC with twisted pairs and UL/CE/PTLC Approvals

---

Approvals	cULus PLTC UL Type CM cURus AWM II A/B NEC 725, 760, 800 Class 1 Div. 2 (PLTC use only)
UL style	AWM 2464
Conformity	CE REACH RoHS
Burning behavior according to	UL VW-1 UL FT4
Oil resistant according to	Oil Res II

---

## General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

---

## Symbols



10.03.2017 – Subject to technical modification

Part-No. A3142208

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY