

# Technical data sheet · LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals

Flexible Tray Cable · Unshielded



|                       |          |                         |
|-----------------------|----------|-------------------------|
| <b>Identification</b> | Type     | SI N TRAY-ER 5×AWG14 SW |
|                       | Part-No. | A3221405                |

|  |   |  |
|--|---|--|
| <b>Use/Application/Characteristics</b> |   |  |
| Application                            | <ul style="list-style-type: none"> <li>• Multi-conductor cable for tray applications, with <b>exposed run</b> (open wiring) approval</li> <li>• Compliant with <b>NFPA 79</b> for machine tool wiring</li> <li>• <b>TC-ER</b> for use with cable trays <b>without conduit</b>, which can reduce material and labor costs</li> <li>• Machine tools, machine and plant construction, HVAC technology, assembly and production lines, and other industrial applications</li> <li>• WTTC – wind turbine tray cable rating for use in wind power generation</li> <li>• Dry, damp and wet conditions</li> </ul> |  |
| Characteristics                        | <ul style="list-style-type: none"> <li>• Flexible design with Nylon for crush impact resistance per UL 1277 and easy installation</li> <li>• Specially formulated jacket for oil resistance</li> <li>• Non-wicking fillers</li> <li>• Sunlight resistant</li> <li>• Direct burial</li> <li>• UL Type TC-Exposed Run</li> <li>• Talc free</li> <li>• Silicone free</li> </ul>  |  |

|                     |                     |
|---------------------|---------------------|
| <b>Construction</b> |                     |
| Description         | SILFLEX TRAY-ER PVC |

11.03.2017 – Subject to technical modification

Part-No. A3221405

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals

---

|                                    |                |
|------------------------------------|----------------|
| Number of conductors/cross-section | 5×AWG14        |
| Jacket material                    | PVC            |
| Jacket color                       | black RAL 9005 |
| Outer Ø                            | 10.4 mm        |
| Outer Ø                            | 0.41 inches    |
| Weight                             | 18.2 kg/100 m  |
| Weight                             | 125 Lbs/Mft    |
| Cu-Index                           | 9.5 kg/100 m   |
| Cu-Index                           | 64 Lbs/Mft     |

## Element 1

|                        |  |
|------------------------|--|
| Element construction   | AWG14/5C   |
| Conductor construction | AWG 14 (41/30)                                   |
| Conductor              | AWG conductor<br>CU-wire bare                    |
| Conductor category     | feindrähtig                                      |
| Conductor marking      | black<br>with white number print<br>green/yellow |
| Conductor insulation   | PVC/Nylon<br>THHN – THWN                         |

## overall construction

|                        |                                |
|------------------------|--------------------------------|
| Jacket characteristics | Oil resistant<br>Silicone-free |
|------------------------|--------------------------------|

---

## Technical data

|                              |                            |
|------------------------------|----------------------------|
| Rated voltage                | 600 V TC-ER<br>1000 V WTTC |
| Temperature range fixed      | -40 °C ... +90 °C          |
| Minimum bending radius fixed | 4×D                        |

## Element 1

|                      |          |
|----------------------|----------|
| Element construction | AWG14/5C |
|----------------------|----------|

---

## Approvals/Standards

---

11.03.2017 – Subject to technical modification

Part-No. A3221405

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


# Technical data sheet · LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals

|                            |  |
|----------------------------|--|
| Approvals                  | TC-ER<br>cURus<br>cULus<br>UL Type MTW or DP-1<br>WTTC<br>Class 1 Div. 2 per NEC<br>Art. 336, 392, 501<br>cUL TC<br>CIC FT4<br>UL 1277 |
| Conformity                 | CE<br>REACH<br>RoHS  |
| Oil resistant according to | Oil Res II   |

## General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

## Symbols



11.03.2017 – Subject to technical modification

Part-No. A3221405

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY