

Technical data sheet · LÜTZE SILFLEX® Tray-ER Blue PVC with UL/TC-ER/CE Approvals, Blue Conductors for 24 V Applications



Flexible Control and Tray Cable ·
Unshielded

Identification	Type	SI N TRAY-ER Blue 3×AWG18 GR
	Part-No.	A3251803

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Multi-conductor cable for tray applications, with exposed run (open wiring) approval • Machine tools, machine and plant construction, HVAC technology, assembly and production lines, and other industrial applications • Automotive applications with 24 Volt • MTW rating as required per NFPA 79 for machine tool wiring • TC-ER for use on machines and in cable trays without conduit • Dry, damp and wet conditions
Characteristics	<ul style="list-style-type: none"> • Flexible design with Nylon for crush impact resistance per UL 1277 and easy installation • Specially formulated jacket for oil resistance • Non-wicking fillers • Sunlight resistant • Direct burial • UL Type TC-Exposed Run • Talc free • Silicone free

Construction

Description	SILFLEX TRAY-ER BLUE PVC
Number of conductors/cross-section	3×AWG18

11.03.2017 – Subject to technical modification

Part-No. A3251803

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SILFLEX® Tray-ER Blue PVC with UL/TC-ER/CE Approvals, Blue Conductors for 24 V Applications

Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	7.5 mm
Outer Ø	0.297 inches
Weight	47 Lbs/Mft
Cu-Index	18 Lbs/Mft

Element 1

Element construction	AWG18/3C
Conductor construction	AWG 18 (19/30)
Conductor	AWG conductor CU-wire bare
Conductor category	feindrähtig
Conductor marking	blue with white number print green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

overall construction

Jacket characteristics	Oil resistant Silicone-free
------------------------	--------------------------------

Technical data

Rated voltage	600 V TC-ER 600 V UL AWM
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	4×D

Element 1

Element construction	AWG18/3C
----------------------	----------

Approvals/Standards

Approvals	TC-ER cURus cULus UL Type MTW or DP-1 Class 1 Div. 2 per NEC Art. 336, 392, 501 UL 1277 cUL TC CIC FT4
-----------	--------------------------------------------------------------------------------------------------------------------------------

11.03.2017 – Subject to technical modification

Part-No. A3251803

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · LÜTZE SILFLEX® Tray-ER Blue PVC with UL/TC-ER/CE Approvals, Blue Conductors for 24 V Applications

Conformity	CE REACH RoHS
Oil resistant according to	Oil Res I

General

Note	***
Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



11.03.2017 – Subject to technical modification

Part-No. A3251803

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk