

## **MSVD POWER SOCKET NEMA (GFCI)**

Mounting rail


USA (2 × NEMA-GFCI 5-15) (Ground Fault Circuit Interrupter) Screw terminals LED (yellow)

Each socket can be loaded with 15 A, however, the total load of both sockets must be below 30 A.

## Link to Product

Illustration





Product may differ from Image

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected

## Approvals



General data	
Mounting method	DIN-rail mountable (EN 60715)
Connection	Screw terminals: max. 6 mm <sup>2</sup>
Dimensions H × W × D	126×64×55 mm
Technical Data	
Operating voltage	max. 125 V AC
Operating current	max. 15 A
Trip level	46 mA
Commercial data	
country of origin	CZ
customs tariff number	85369010
minimum order quantity	1

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com