

## MEN POWER SUPPLY 1/2-PHASE, SMOOTHED

IN: 230/400+/-15VAC OUT: :24V/7,5ADC


Current: 7.5 A


Output rating: 180 W

This power supply units meet the (EN 61000-3-2) standard for harmonic current.

### [Link to Product](#)

#### Illustration





Product may differ from Image

### Approvals



### Input

Input voltage	230/400 ±15 V AC
Input current	1.44 A (230 V AC); 0.84 A (400 V AC)
Input fuse (external)	2 A (230 V AC); 1.25 A (400 V AC)
Frequency	50...60 Hz

### General data

Standards	EN 61558-2-6, EN 62041 category I, EN 55011 B, EN 61000-3-2
Mounting method	Key-hole mounting
Dimensions H × W × D	103×105×150.5 mm
Fixing centers a × b × c	86.5×90×5.8 mm
Temperature range	-20...+60 °C, no condensation

### Output

Output voltage	24 V DC (SELV)
Output current (Ta 60/40 °C)	max. 7.5 A (230 V AC); 9 A (400 V AC)
Ripple	max. 5 %rms
Output fuse	15 A (automotive fuse FKS)
Output filter	LED, VDR and smoothing capacitor

### Commercial data

country of origin	CZ
customs tariff number	85044090
minimum order quantity	1