

MTL 1-PHASE CONTROL AND ISOLATION TRANSFORMER


P: 25VA IN: 230/400VAC +/- 15VAC OUT: 2x115VAC

25 VA

Isolation class T 60/B

[Link to Product](#)

Illustration



Product may differ from Image

Approvals



Input

Input voltage	230/400 ±15 V AC
Frequency	50...60 Hz
Input current	0.19 A (230 V AC); 0.11 A (400 V AC)
Inrush current	1.62 A (230 V AC); 0.94 A (400 V AC)
Short-circuit current	1.78 A (230 V AC); 1.03 A (400 V AC)

General data

Test isolation voltage	4 kV (prim./sec.)
Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Drill hole Ø	5.5×9 mm
Mounting method	DIN-rail mountable TH35-15 (EN 60715) or for key-hole mounting
Fixing centers a × b × c	96×60×5.5 mm
Dimensions H × W × D	108×87×98 mm
Temperature range	-20...+60 °C, no condensation

Technical Data

LED display	LED (green) for input voltage
-------------	-------------------------------

Output

Output voltage	1 × 230, 1 × 115, 2 × 115 V AC
----------------	--------------------------------

Commercial data

country of origin	CZ
customs tariff number	85043180
minimum order quantity	1