

stay connected

TELEMECANIQUE CONTACTOR SUPPRESSOR

Varistor, 110VAC/DC

110 V AC/DC VDR

For other configurations and voltages, please inquire

Link to Product

Illustration




VDR

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com





Product may differ from Image

Approvals



Appropriate contactors	
	LC 1 D09D38, LC 1 DT20, DT40, LC 2 D09D38
General data	
Dimensions H × W × D	15×36×38 mm
Temperature range	-20+70 °C
Technical Data	
Damping factor	approx. 1.5 × UN
Material	Flame retardant plastic acc. to (UL 94)
Connection wires	self-securing cable forks
Commercial data	
country of origin	CZ
customs tariff number	85363010
minimum order quantity	1

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com