

MODLINK MSDD DBL COMBI INSERT USA NEMA 5-15

1xRJ45 fem./fem. + 1xUSB-A fem./fem. + 1x3A fuse

- 1 × NEMA 5-15 (screw terminals)
- 1 × RJ45, 8-pole metal, CAT5e (female/female)
- 1 × USB (female/female) form A
- 1 × fuse (3 A)

Link to Product

Illustration



Product may differ from Image

Approvals



General data

Dimensions H × W × D 88×116×72 mm

Frame

suitable for mounting with wall thickness 1...5 mm

Protection IP65

Housing Zinc die-casting, with surface finishing

Temperature range -10...+60 °C (storage temperature -25...+60 °C)

Shielded yes

Communication inserts

Article number 4000-68000-4200000

Operating voltage	max. 125 V AC
Operating current	max. 15 A
Fuse	3 A
Connection	Screw terminals
Mounting depth mounted	approx. 70 mm

RJ45

Operating voltage	max. 30 V AC/42.4 V DC
Operating current	max. 175 mA
Locking of ports	staple
Specification	CAT6, class EA (ISO/IEC 11801:2002), (EN 50173-1)
Mounting depth mounted	approx. 32 mm
Shielded	yes

Commercial data

country of origin	CZ
customs tariff number	85366990
minimum order quantity	1