

MODLINK MSDD FRAME SINGLE METAL


Nickeled/transparent

Frame: metal, matte nickel plated Lid: plastic, transparent

Link to Product

Illustration





Product may differ from Image

General data

Dimensions $H \times W \times D$

120×65×38 mm

Frame

suitable for mounting with wall thickness

1...5 mm

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



	stay connec
Protection	IP65
Housing	Zinc die-casting, with surface finishing
Temperature range	-10+60 °C (storage temperature -25+60 °C)
Shielded	yes, only with shielded inserts
Commercial data	
country of origin	DE
customs tariff number	85389099
minimum order quantity	1

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com