

stay connected

M8 FEMALE SNAP-IN 0°


PUR 4x0.25 YELLOW, 1.5m

M8 Male straight 4-pole Snap In

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product


Illustration






stay connected

Female





Product may differ from Image

Approvals







* only for products with UL/CSA approvaled cable

Form	
Form	08221
Cables	
Cable number	021
No./diameter of wires	4 × 0.25 mm ²
Wire isolation	PVC (br, wh, bl, bk)
C-track properties	2 Mio.
Jacket Color	yellow
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR/PVC (UL/CSA)
Outer Ø	approx. 4.8 mm
Bend radius (fixed)	10 × outer Ø
Bend radius (moving)	15 × outer Ø
Temperature range (fixed)	-30+80 °C

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected

Temperature range (mobile)	-5+80 °C
General data	
Temperature range	-25+85 °C, depending on cable quality
Technical Data	
Operating voltage	max. 30 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Snap In
Protection	IP65
Commercial data	
country of origin	DE
customs tariff number	85444290
minimum order quantity	1