

stay connected

## M8 female 90° snap-in with cable LED

PVC 3x0.25 ye UL/CSA 3m


M8
Female 90° with LED
3-pole with 2 × LED (PNP)
Snap In

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

## **Link to Product**

#### Illustration









stay connected

# **Female**





Product may differ from Image

### **Approvals**





\* only for products with UL/CSA approvaled cable

Form		
Form	08281	
Cables		
Cable number	010	
No./diameter of wires	3 × 0.25 mm <sup>2</sup>	
Wire isolation	PVC (br, bl, bk)	
Jacket Color	yellow	
Shore hardness outer jacket	85 ± 5A	

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected
----------------

Material (jacket)	PVC (UL/CSA)
Outer Ø	approx. 4.5 mm
Bend radius (fixed)	5 × outer Ø
Bend radius (moving)	10 × outer Ø
Temperature range (fixed)	-30+80 °C
Temperature range (mobile)	-5+80 °C
General data	
Temperature range	-25+85 °C, depending on cable quality
Technical Data	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Snap In
Protection	IP65
Commercial data	
country of origin	DE
customs tariff number	85444290
minimum order quantity	1