

stay connected

### M8 FEMALE 90° SNAP-IN LED


PUR 3x0.25 GRAY, 7.5m


M8
Female 90° with LED
3-pole with 2 × LED (PNP)
Snap In

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

## **Link to Product**

#### Illustration









stay connected

# **Female**





Product may differ from Image

## **Approvals**





\* only for products with UL/CSA approvaled cable

Form		
Form	08281	
Cables		
Cable number	220	
No./diameter of wires	3 × 0.25 mm <sup>2</sup>	
Wire isolation	PVC (br, bl, bk)	
C-track properties	2 Mio.	
Jacket Color	gray	

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected

Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR/PVC (UL/CSA)
Outer Ø	approx. 4.5 mm
Bend radius (fixed)	10 × outer Ø
Bend radius (moving)	15 × outer Ø
Temperature range (fixed)	-30+80 °C
Temperature range (mobile)	-5+80 °C
General data	
Temperature range	-25+85 °C, depending on cable quality
Technical Data	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Snap In
Protection	IP65
Commercial data	
country of origin	DE
customs tariff number	85444290
minimum order quantity	1