

stay connected

M8 FEMALE 90° SNAP-IN LED

PUR 3x0.25 black 5m


M8
Female 90° with LED
3-pole with 2 × LED (PNP)
Snap In

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration









stay connected

Female





Product may differ from Image

Approvals





* only for products with UL/CSA approvaled cable

| Form | |
|-----------------------|------------------------------|
| Form | 08281 |
| Cables | |
| Cable number | 620 |
| No./diameter of wires | $3 \times 0.25 \text{ mm}^2$ |
| Wire isolation | PVC (br, bl, bk) |
| C-track properties | 2 Mio. |
| Jacket Color | black |

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected

| Shore hardness outer jacket | 85 ± 5A |
|-------------------------------|---------------------------------------|
| Material (jacket) | PUR/PVC (UL/CSA) |
| Outer Ø | approx. 4.5 mm |
| Bend radius (fixed) | 10 × outer Ø |
| Bend radius (moving) | 15 × outer Ø |
| Temperature range (fixed) | -30+80 °C |
| Temperature range (mobile) | -5+80 °C |
| General data | |
| Temperature range | -25+85 °C, depending on cable quality |
| Technical Data | |
| Operating voltage | 24 V DC ±25 % |
| Operating current per contact | max. 4 A |
| Locking of ports | Snap In |
| Protection | IP65 |
| Commercial data | |
| country of origin | DE |
| customs tariff number | 85444290 |
| minimum order quantity | 1 |