

M12 female 0° with cable

PVC 4x0.34 ye UL/CSA 2m


M12

Female straight



4-pole

Art.-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request. Further cable lengths on request.

Link to Product**Illustration**

Female



Product may differ from Image

Approvals



* only for products with UL/CSA approved cable

Form

Form 12221

Cables

Cable number 014

No./diameter of wires 4 x 0.34 mm²

Wire isolation PVC (br, wh, bl, bk)

Jacket Color yellow

Shore hardness outer jacket 85 ± 5 A

Material (jacket) PVC (UL/CSA)

Outer Ø approx. 5.0 mm

Bend radius (fixed) 5 x outer Ø

Bend radius (moving) 10 x outer Ø

Temperature range (fixed) -30...+80 °C

Temperature range (mobile) -5...+80 °C

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

General data

Temperature range	-25...+85 °C, depending on cable quality
-------------------	--

Technical Data

Operating voltage	max. 250 V AC/DC
Operating voltage (only UL listed)	max. 30 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP66K, IP67 inserted and tightened (EN 60529)
Locking material	Zinc die casting, matte nickel plated

Commercial data

country of origin	DE
customs tariff number	85444290
minimum order quantity	1