

**M12 FEMALE 90°**

PUR 5X0.34 GRAY, UL/CSA, drag ch 7.5m

M12

Female 90°

5-pole

Art.-No. 7005 - M12 Lite - (plastic hexagonal screw) on request


Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request. Further cable lengths on request.

**[Link to Product](#)****Illustration**

|   |   |                |
|---|---|----------------|
| 1 | ↷ | brown (+)      |
| 2 | ↷ | white (N/C)    |
| 4 | ↷ | black (N/O)    |
| 3 | ↷ | blue (-)       |
| 5 | ↷ | gn/ye (* gray) |


(\* for cable type 126, 732, 219, 619)

# Female



Product may differ from Image

Approvals



\* only for products with UL/CSA approved cable

Form

Form 12361

Cables

|                       |                           |
|-----------------------|---------------------------|
| Cable number          | 235                       |
| No./diameter of wires | 5 × 0.34 mm²              |
| Wire isolation        | PP (br, wh, bl, bk, gnye) |
| C-track properties    | 5 Mio.                    |
| Torsion               | 2 Mio. ± 180 °/m          |
| Jacket Color          | gray                      |

|                             |                |
|-----------------------------|----------------|
| Shore hardness outer jacket | 90 ± 5A        |
| Material (jacket)           | PUR (UL/CSA)   |
| Outer Ø                     | approx. 5.0 mm |
| Bend radius (fixed)         | 5 × outer Ø    |
| Bend radius (moving)        | 10 × outer Ø   |
| Temperature range (fixed)   | -40...+80 °C   |
| Temperature range (mobile)  | -25...+80 °C   |

**General data**

|                   |                                          |
|-------------------|------------------------------------------|
| Temperature range | -25...+85 °C, depending on cable quality |
|-------------------|------------------------------------------|

**Technical Data**

|                               |                                                                   |
|-------------------------------|-------------------------------------------------------------------|
| Operating voltage             | max. 125 V AC/DC                                                  |
| Operating current per contact | max. 4 A                                                          |
| Locking of ports              | Screw thread M12 × 1 mm (recommended torque 0.6 Nm) self-securing |
| Protection                    | IP66K, IP67 inserted and tightened (EN 60529)                     |

**Commercial data**

|                        |          |
|------------------------|----------|
| country of origin      | CZ       |
| customs tariff number  | 85444290 |
| minimum order quantity | 1        |