

**M12 FEMALE 90° SHIELDED**


PUR 5X0.34 shielded GRAY, UL/CSA 8.3m

M12

Female 90°

5-pole, shielded

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request. Further cable lengths on request.

**[Link to Product](#)****Illustration**

1	↷		brown (+)
2	↷		white (N/C)
4	↷		black (N/O)
3	↷		blue (-)
5	↷		gn/ye (gray*)
			shield

(\* for cable type 203, 603, 243, 643)

# Female



Product may differ from Image

### Approvals



\* only for products with UL/CSA approved cable

### Form

Form 13281

### Cables

Cable number	949
No./diameter of wires	5 × 0.34 mm²
Wire isolation	PP (br, wh, bl, bk, gr)
C-track properties	2.5 Mio.

Jacket Color	gray
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR (UL/CSA)
Outer Ø	approx. 6.5 mm
Bend radius (fixed)	5 × outer Ø
Bend radius (moving)	10 × outer Ø
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-20...+80 °C
Shielded	yes

#### General data

Temperature range	-25...+85 °C, depending on cable quality
-------------------	--

#### Technical Data

Operating voltage	max. 60 V AC/DC
Operating voltage (only UL listed)	max. 30 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 × 1 mm (recommended torque 0.6 Nm) self-securing
Locking material	Zinc die casting, matte nickel plated
Protection	IP66K, IP67 inserted and tightened (EN 60529)

#### Commercial data

country of origin	DE
customs tariff number	85444290
minimum order quantity	1