


**M12 male receptacle B coded rear mount Profibus**


PUR 1x2xAWG24 shielded vt UL/CSA+dragchain 0,3m

Flange M12 male  
B-coded, 2-pole, shielded  
Rear mounting  
Mounting nut  
With open ended wires

Further cable lengths on request. The resistance to aggressive media should be individually tested for your application. Further details on request.


[Link to Product](#)**Illustration**

# Male



Product may differ from Image

## Approvals



## More Info



## Form

Form 14131

## Cables

Cable number	841
No./diameter of wires	1 × 2 × Ø 0.64 mm, (violet)
Wire isolation	PE (rd, gn)
C-track properties	5 Mio.
Jacket Color	violet
Shore hardness outer jacket	87 ± 3A
Material (jacket)	PUR (UL/CSA)

Outer Ø	approx. 7.7 mm
Bend radius (fixed)	7.5 × outer Ø
Bend radius (moving)	12 × outer Ø
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-20...+60 °C
Shielded	yes

#### Technical Data

Operating voltage	max. 60 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 × 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP66K, IP67 inserted and tightened (EN 60529)
Material	CuZn, nickel plated

#### Commercial data

country of origin	DE
customs tariff number	85444290
minimum order quantity	1