

M12 FEMALE 0° SHIELDED

PUR 8x0,25 shielded GRAY, drag ch 4m

M12

Female straight

8-pole, shielded

Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request. Further cable lengths on request.

[Link to Product](#)**Illustration**

1	↷			brown
2	↷			white
3	↷			blue
4	↷			black
5	↷			gray
6	↷			pink
7	↷			violet
8	↷			orange
				shield

Female



Product may differ from Image

Approvals



Form

Form 17121

Cables

Cable number	294
No./diameter of wires	8 × 0.25 mm²
Wire isolation	PP (br, wh, bl, bk, gr, pk, vi, or)
C-track properties	5 Mio.
Torsion	2 Mio. ± 30°/m
Jacket Color	gray
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR (UL/CSA)
Outer Ø	approx. 7.0 mm
Bend radius (fixed)	5 × outer Ø
Bend radius (moving)	10 × outer Ø
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-20...+80 °C

Shielded yes

General data

Temperature range -25...+85 °C, depending on cable quality

Technical Data

Operating voltage max. 30 V AC/DC

Operating current per contact max. 2 A

Locking of ports Screw thread M12 × 1 mm (recommended torque 0.6 Nm) self-securing

Protection IP66K, IP67 inserted and tightened (EN 60529)

Commercial data

country of origin DE

customs tariff number 85444290

minimum order quantity 1