

M23 female 0° with cable

PUR 6x0.34+3x0.75 gy drag chain 15m

M23

Female straight

12-pole

9-pole used


for 6-way distribution box, 4-pole

Further cable lengths on request. Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)**Illustration**

1	white
2	green
3	yellow
4	gray
5	pink
6	red
11	brown 0.75 mm ²
9	blue 0.75 mm ²
12	green / yellow 0.75 mm ²

Female



Product may differ from Image

Form	
Form	23031
Cables	
Cable number	355
No./diameter of wires	6×0.34 + 3×0.75 mm²
Wire isolation	PVC (ye, wh, gn, gr, pk, rd+br, bl, gnye)
C-track properties	2 Mio.
Jacket Color	gray
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR/PVC
Outer Ø	approx. 9.1 mm
Bend radius (fixed)	10 × outer Ø
Bend radius (moving)	12 × outer Ø
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+70 °C
General data	
Temperature range	-25...+85 °C, depending on cable quality
Technical Data	
Operating voltage	125 V AC/DC
Operating current per contact	max. 7.5 A
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

Locking of ports

Screw thread M23 × 1 mm

Commercial data

country of origin

DE

customs tariff number

85444290

minimum order quantity

1