

M23 FEMALE 19 POLE 0°

PUR 8x0,34+3X0.75 shielded GRAY, UL 25m

M23

Shield on M23 cap nut

Female straight

19-pole

11-pole used


for 4-way distribution boxes, 5-pole

Further cable lengths on request. Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product**Illustration**

15	white
7	gray/ pink
5	green
4	red/ blue
16	yellow
8	white/ green
3	gray
14	brown/ green
19	brown 0.75 mm ²
6	blue 0.75 mm ²
12	green/ yellow 0.75 mm ²
Shield	

Female



Product may differ from Image

Form	
Form	23711
Cables	
Cable number	373
No./diameter of wires	8×0.34 + 3×0.75 mm²
Wire isolation	TPE (grpk, wh, rdbl, gn, whgn, ye, brgn, gr, br, bl, gnye)
C-track properties	5 Mio.
Jacket Color	gray
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR (UL/CSA)
Outer Ø	approx. 9.3 mm
Bend radius (fixed)	10 × outer Ø
Bend radius (moving)	12 × outer Ø
Temperature range (fixed)	-40...+90 °C
Temperature range (mobile)	-40...+90 °C
Shielded	yes
General data	
Temperature range	-25...+85 °C, depending on cable quality
Technical Data	
Operating voltage	max. 125 V AC/DC
Operating current per contact	max. 10 A
Locking of ports	Screw thread M23 × 1 mm

Protection IP67 inserted and tightened (EN 60529)

Commercial data

country of origin DE

customs tariff number 85444290

minimum order quantity 10