

stay connected

Push Pull RJ45 with cable, Profinet

PUR 2x2xAWG22 shielded gn UL/CSA+dragchain 25m


Push Pull, RJ45 Male straight 4-pole, shielded

Further cable lengths on request. Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration









stay connected







Height: 22 mm

Product may differ from Image

More Info



99631
796
2 × 2 × AWG22
PE (wh, ye, bl, or)
2 Mio.
green
90 ± 5A
PUR (UL/CSA)
approx. 6.7 mm
5 × outer Ø
15 × outer Ø
-40+80 °C

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connecte	₽d
---------------	----

	PERSONAL PROPERTY OF THE PROPERTY OF THE PERSONAL PROPERTY OF THE PERSO
Temperature range (mobile)	-20+60 °C
Shielded	yes
General data	
Temperature range	-40+70 °C, depending on cable quality
Technical Data	
Operating voltage	max. 60 V DC
Operating current per contact (20 °C)	max. 1.75 A
Locking of ports	Push Pull
Protection	IP67 inserted and tightened (EN 60529)
Commercial data	
country of origin	DE
customs tariff number	85444290
minimum order quantity	1