


MQ12 FEMALE 90°

PVC 4X0.34 black 30m

Female 90° 4-pole

Further cable lengths on request. Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product





The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16



stay connected

Female





Product may differ from Image

Approvals	
Form	
Form	12341
Cables	
Cable number	614
No./diameter of wires	4 × 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk)
Jacket Color	black
Shore hardness outer jacket	85 ± 5A
Material (jacket)	PVC (UL/CSA)
Outer Ø	approx. 5.0 mm
Bend radius (fixed)	$5 \times \text{outer } \emptyset$

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



stay connected

Bend radius (moving)	10 × outer Ø	
Temperature range (fixed)	-30+80 °C	
Temperature range (mobile)	-5+80 °C	
General data		
Temperature range	-25+85 °C, depending on cable quality	
Technical Data		
Operating voltage	max. 250 V AC/DC	
Operating current per contact	max. 4 A	
Locking of ports	Quick connection, 1/4 turn	
Protection	IP67 inserted and tightened (EN 60529)	
Commercial data		
country of origin	DE	
customs tariff number	85444290	
minimum order quantity	1	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com