



Model Number


GLV12-8-200/36/40b/92

Diffuse mode sensor
with 4-pin, M12 x 1 connector


Features

- M12 threaded housing made of brass, nickel plated
- Visible red light
- Light/dark ON, programmable
- Degree of protection IP67


Dimensions



Electrical connection



Pinout



Release date: 2014-04-07 10:39 Date of issue: 2014-04-22 08:49:45_eng.xml

Technical data**General specifications**

Detection range	0 ... 200 mm
Adjustment range	20 ... 200 mm
Reference target	standard white 200 mm x 200 mm
Light source	LED, 640 nm
Light type	modulated visible red light
Ambient light limit	20000 Lux

Indicators/operating means

Function indicator	LED yellow: switching state
Control elements	Detection range adjuster

Electrical specifications

Operating voltage	U_B	10 ... 30 V DC
Ripple		10 %
No-load supply current	I_0	≤ 20 mA
Time delay before availability	t_v	≤ 25 ms

Input

Control input	light on +UB dark on: 0 V
---------------	------------------------------

Output

Switching type	light/dark on	
Signal output	1 NPN output, short-circuit protected, reverse polarity protected, open collector	
Switching voltage	max. 30 V DC	
Switching current	max. 300 mA	
Voltage drop	U_d	≤ 3 V
Switching frequency	f	≤ 700 Hz
Response time		≤ 0.7 ms

Standard conformity

Standards	EN 60947-5-2
-----------	--------------

Ambient conditions


Ambient temperature	-25 ... 55 °C (-13 ... 131 °F)
Storage temperature	-40 ... 70 °C (-40 ... 158 °F)

Mechanical specifications

Degree of protection	IP67
Connection	4-pin, M12 x 1 connector
Material	
Housing	brass, nickel-plated
Optical face	PMMA
Mass	15 g

Approvals and certificates

CCC approval	CCC approval / marking not required for products rated ≤ 36 V
Approvals	CE

Curves/Diagrams**Accessories****V1-G-2M-PUR**

Female cordset, M12, 4-pin, PUR cable

V1-W-2M-PUR

Female cordset, M12, 4-pin, PUR cable


BF 12

Mounting flange, 12 mm

BF 5-30

Universal mounting bracket for cylindrical sensors with a diameter of 5 ... 30 mm

Other suitable accessories can be found at www.pepperl-fuchs.com



Release date: 2014-04-07 10:39 Date of issue: 2014-04-22 084945_eng.xml

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com