


**Dimensions**



**Model Number**


**OCS2000-M1K-N2**

NAMUR retroreflective sensor, special design, 2 m detection range, red light, light/dark ON, DC version, NAMUR output, terminal compartment

**Features**

- ATEX-, IECEx approval for zone 20 (Dust) and zone 1 (Gas)
- Intrinsically safe, Ex op is ia IIC T6 Gb/IIIC T 135 °C Da
- Glare protected with polarization filter
- Adjustable sensor head
- Scratch resistant mineral glass lens

**Electrical connection**



Release date: 2013-09-03 17:59 Date of issue: 2013-09-03 106529\_eng.xml

**Technical data****General specifications**

Effective detection range	0 ... 2 m
Reflector distance	100 ... 2000 mm
Threshold detection range	2 m
Reference target	Retro-reflector C110-2
Light source	LED , 660 nm
Light type	modulated visible red light
Approvals	CE
Ambient light limit	≤ 10000 Lux sun light ≤ 7500 Lux halogen light

**Functional safety related parameters**

MTTF <sub>d</sub>	1319 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

**Indicators/operating means**

Function display	LED yellow: switching state
------------------	-----------------------------

**Electrical specifications**

Operating voltage	U <sub>B</sub>	6 ... 20 V DC (R <sub>i</sub> approx. 0 Ohm)
Ripple		5 %
Time delay before availability	t <sub>v</sub>	20 ms

**Output**

Switching type	light/dark on, programmable	
Signal output	1 NAMUR output NC/NO programmable	
Switching voltage	8 V DC (R <sub>i</sub> approx. 1 kΩ)	
Switching frequency	f	≤ 100 Hz

**Current consumption**

Reference target detected	connection 1, 2: ≥ 2.2 mA connection 1, 4: ≤ 1 mA
Reference target not detected	connection 1, 2: ≤ 1 mA connection 1, 4: ≥ 2.2 mA

Response time	5 ms
---------------	------

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
Storage temperature	-40 ... 80 °C (-40 ... 176 °F)

**Mechanical specifications**

Protection degree	IP67 according to EN 60529, Class II insulation
Connection	M16&nbsp;terminal compartment, core cross-section ≤ 2.5 mm <sup>2</sup>
Material	
Housing	PBT
Optical face	Scratch resistant mineral glass lens
Mass	100 g

**Compliance with standards and directives**

Standard conformity	
Product standard	EN 60947-5-2

Standards	DIN EN 60947-5-6
-----------	------------------

**Approvals and certificates****FM approval**

Approved for	IS / I,II,III / 1 / ABCDEFG / T5 - 116-0110; Entity NI / I / 2 / ABCD / T6 Entity Parameters: V <sub>Max</sub> = 12.6 V, I <sub>Max</sub> = 20 mA, C <sub>i</sub> = 1.11 μF, L <sub>i</sub> = 0 mH (Groups A, B, C, D, E, F, G). V <sub>Max</sub> = 15.5 V, I <sub>Max</sub> = 52 mA, C <sub>i</sub> = 1.11 μF, L <sub>i</sub> = 0 mH (Groups C, D, E, F, G).
--------------	---



**CSA approval**

Approved for	Class I, Division 2, Groups A, B, C and D Rated 20V (max), 50mA. These sensors are suitable for installation in (or through the wall of) a suitable enclosure with provision for connection of rigid metal conduit, as acceptable to the local inspection authority having jurisdiction.
--------------	--

**CCC approval**

CCC approval	CCC approval / marking not required for products rated ≤36 V
--------------	--

Curves / Diagrams



Release date: 2013-09-03 17:59 Date of issue: 2013-09-03 106529\_eng.xml

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com