




Model Number

LHE 00-1,1-1,0-20M4

Glass fiber optic - thru-beam with silicon covering

Threading M4

Features

- Chemical-resistant
- Thread M2.6 / M4
- High temperature rated to 180 °C
- High flexible

Series

Fiber optic amplifiers

Device series SU18 ; SU18/35 ; SU19

Description

Attention:

Fibre optics must not be twisted or kinked. Excessive tensile loads will lead to destruction.



Accessories

K-LA01

Auxiliary lens

K-LA02

Auxiliary lens 90°

K-LA06

Auxiliary lens M4

OMH-LL-M4

Mounting bracket

KM4-0,5

Metal protection for plastic fiber optics
M4 x 0.5 m

KM4-1,0

Metal protection for plastic fiber optics
M4 x 1.0 m

Technical data

General specifications

Detection range	SU18: 195 mm SU18/35: 710 mm SU19: 195 mm
Fiber optic length	l 1000 mm
Fiber optic diameter	d 3 mm
Adapter form	00
End piece	thread
Bending radius	4 mm static

Fiber bundle diameter	1.1 mm
Angle of divergence	approx. 68 °

Ambient conditions

Ambient temperature	-20 ... 85 °C (-4 ... 185 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
---------------------	--

Mechanical specifications

Material	
Optical face	glass
Sheathing	silicon
Core	Glass fiber
End piece	Stainless steel 1.4305 / AISI 303
Adapter	Stainless steel
Extraction force	50 N

General information

Scope of delivery	Fiber optic cables packaged individually
-------------------	--

Dimensions

