



Model Number

LHE 00-1,1-1,0-WC3

Glass fiber optic - thru-beam with silicon covering

Features

- Chemical-resistant
- High temperature rated to 180 °C
- High flexible

Series

Fiber optic amplifiers

Device series SU18 ; SU18/35 ; SU19

Description

Attention:

Fibre optics must not be twisted or kinked. Excessive tensile loads will lead to destruction.



Technical data

General specifications

Detection range		SU18: 195 mm SU18/35: 710 mm SU19: 195 mm
Fiber optic length	l	1000 mm
Fiber optic diameter	d	3 mm
Adapter form		00
End piece		Thread / cylindrical right angle
Bending radius		4 mm static 8 mm 250.000 cycles dynamic
Fiber bundle diameter		1.1 mm
Angle of divergence		approx. 68 °

Ambient conditions

Ambient temperature		-20 ... 85 °C (-4 ... 185 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
---------------------	--	--

Mechanical specifications

Material		
Optical face		glass
Sheathing		silicon
Core		Glass fiber
End piece		Stainless steel 1.4305 / AISI 303
Adapter		Stainless steel
Extraction force		50 N

General information

Scope of delivery		Fiber optic cables packaged individually
-------------------	--	--

Dimensions

