# VAZ-FLASH-70MM-YE



# CE

#### Model number

#### VAZ-FLASH-70MM-YE

Stack light LED flashing light element, yellow

#### Features

- Large diameter ٠
- Modular design •
- Flexible combination of signal ele-• ments
- Bayonet system for simple mounting ٠ and dismounting
- Long lifetime

### **Function**

The LED flashing light element converts electrical signals to optical signals. It has been designed and tested according to EN 60947-5-1.

The light element is available in various colours and the bayonet type connector allows easy installation on the corresponding terminal. The modular design permits userdefined combinations and reduces operation costs and storage costs.

The illuminant based on LED technology is integrated in the spherical cap and features an excellent illumination, good resistance against shock and vibration as well as a long service life, which also means good MTBF figures (Mean Time Between Failures).


#### Matching system components

#### VAZ-CLAMP-70MM

Stack light terminal base with cover plate

#### VAZ-CLAMP-70MM-90°

Stack light terminal base with cover plate



## **Technical data**

Degree of protection

Dimensions

General specifications		
UL File Number		E223176
Color		yellow
Frequency		approx. 1 Hz
Functional safety related parameters		
MTTF <sub>d</sub>		700 a
Electrical specifications		
Rated operating voltage	Ue	24 V DC
Rated operating current	l <sub>e</sub>	35 mA
Protection class		ll
Ambient conditions		
Ambient temperature		-20 50 °C (-4 122 °F)
Mechanical specifications		
Degree of protection		IP65
Connection		Bayonet system
Life span		Max. 50000 hours = 5.7 years (continuous operation)
Compliance with standards and directi- ves		
Directive conformity		
EMC Directive 2004/108/EC		EN 60947-5-1:2005 EN 60947-1:2007
Standard conformity		

EN 60529:2000

205224\_eng.xml issue: 2014-07-28 Date of Release date: 2014-07-28 13:07

> Refer to "General Notes Relating to Pepperl+Fuchs Product Information" USA: +1 330 486 0001

fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411 fa-info@de.pepperl-fuchs.com



1

Pepperl+Fuchs Group www.pepperl-fuchs.com