



Model Number

LHR 00-0,8-2,0-20M4

Glass fiber optic - diffuse with silicon covering

Threading M4 / M2, 6

Features

- Chemical-resistant
- Thread M2.6 / M4
- High temperature rated to 180 °C
- High flexible

Series

Fiber optic amplifiers

Device series SU18 ; SU18/35 ; SU19

Description

Attention:

Fibre optics must not be twisted or kinked. Excessive tensile loads will lead to destruction.



Accessories

OMH-LL-M4

Mounting bracket

Technical data

General specifications

Sensor range	SU18: 40 mm SU18/35: 195 mm SU19: 40 mm
Fiber optic length	l 2000 mm
Fiber optic diameter	d 3 mm
Adapter form	00
End piece	thread
Bending radius	5 mm static
Fiber bundle diameter	0.8 mm
Fiber configuration	Fv optical separated
Angle of divergence	68 °

Ambient conditions

Ambient temperature	-30 ... 80 °C (-22 ... 176 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
---------------------	---

Mechanical specifications

Material	
Optical face	glass
Sheathing	silicon
Core	Glass fiber
End piece	Stainless steel 1.4305 / AISI 303
Adapter	Stainless steel
Extraction force	50 N

Dimensions

